18/12C Type SOOW Black



PRODUCT DATA SHEET

SOOW portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavy-duty cable service applications. This cable is rated to 600 volts and has a temperature range of -40° C to $+90^{\circ}$ C. These characteristics make SOOW portable cord an excellent choice for mitigating outdoor factors.

Design Number10718Part Number32175217Customer NumberN/A

CONSTRUCTION

Conductor: Stranded bare copper **Conductor Size:** 18AWG, 16/0.254mm **Insulation:** EPDM, oil resistant

Insulation Avg. Thickness: 0.030" (Nom.)
Insulated Conductor O.D: 0.112" (Nom.)

Separator: Non-woven cloth

Jacket Material: CPE, oil resistant


Jacket Avg. Thickness: 0.080"(Nom.)

Overall Diameter: 0.630"(Nom.)

Jacket Color: Black

Print Legend:

ASCENT E486041-11 18 AWG 12/C SOOW (UL) 600V (-40C-90C)--CSA LL603159 FT-2 WATER RESISTANT P-07-KA170009- MSHA --RoHS xxxxxxM



Color Code: Black, White, Red, Green, Orange, Blue, White/Red Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +90°C Operating Voltage: 600V Flame Test: CSA FT2

SAFETY CHARACTERISTICS

Approvals: UL Flexible Cord, Subject 62
CSA Flexible Cord, C22.2 No.49
MSHA Approved

RoHS Compliant

Application: Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History

00 2023/02/20 Initial release

01 2023/02/22 Conductor wire size is added

02 2023/08/25 Core color White/Black is updated to White/Red

Created L. Jian Approved A. Huang



