## 10/5C Type SOOW Black H07RN-F 450/750V 5G6



PRODUCT DATA SHFFT

S00W portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavyduty cable service applications. This cable is rated to 600 volts and has a temperature range of –  $40^{\circ}$ C to  $+90^{\circ}$ C. These characteristics make S00W portable cord an excellent choice for mitigating outdoor factors.

Design Number 10895
Part Number 32187187
Customer Number N/A



Conductor: Stranded bare copper, Class K per ASTM B-174

**Conductor Size:** 10AWG(86/0.30mm) **Insulation:** EPDM, oil resistant **Insulation Thickness:** 1.14mm(Nom.)


Filler: Rubber strip in central Separator: Non-woven tape Jacket Material: CPE, oil resistant Jacket Thickness: 2.41mm(Nom.)

Overall Diameter: Nom20.0mm, Max 20.3mm

Jacket Color: Black

Print Legend:

ASCENT E486041-11 10AWG(6.08mm<sup>2</sup>) 5C SOOW UL 600V (-40C-90C) ---



Color Code: Green/Yellow, Blue, Brown, Black, Grey

## ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +90°C Operating Voltage: 600V Approx. Weight: 660 kg/km

## **SAFETY CHARACTERISTICS**

Flame Test: CSA FT2

**Approvals:** UL Flexible Cord, Subject 62

CSA Flexible Cord, C22.2 No.49

**RoHS Compliant** 

**Application:** Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2023/12/06	Initial release
01	2025/01/13	The KC certification is added into print legend
Cre	ated L. Jian	Approved A. Huang

