
VIDEO DETECTION CABLE

Composite Camera Cable



Cable Identification

Ink jet print on jacket "ADVANCED DIGITAL CABLE, INC. 20 AWG PE Coax + 22 AWG 2 PR IND SHLD PP + 18 AWG 3 CDR PVC - PVC SUN RES/DIR BUR"

Specifications Coax	Specifications Multi-Conductors	Put-Ups
Conductor - 20 AWG Sol BC .032 Braid - 2x95% BC Jacket - LDPE .304 Nominal	Component 1- 18 AWG/3c BC Insulation - PVC .082 Nominal Color Code - Blue, Brown, Green w/Yellow Stripe Component 2- 22 AWG/2 ISP TC Insulation - Polypropylene .046 Nominal Shielding - Aluminum Mylar with drain Color Code - Black/Red. Green/White	Standard Reels 1,000', 2,500', 5,000' Other lengths available. Please consult your factory representa- tive for availability.

PART NO.	COMPONENTS	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
9928	3	.020 PVC	.508 PVC	.340 x .680	8.6 x 17.27	113

Composite Camera Cable - Hi Flex





Cable Identification

Ink jet print on jacket "ADVANCED DIGITAL CABLE, INC. 22 AWG PVC Coax + 22 AWG 2 PR IND SHLD PP + 18 AWG 3 CDR PVC - PVC SUN RES/DIR BUR"

Specifications Coax	Specifications Multi-Conductors	Put-Ups
Conductor - 22 AWG Strd BC .031 Braid - 2x98% TC Jacket - PVC .304 Nominal	Component 1- 18 AWG/3c BC Insulation - PVC .082 Nominal Color Code - Black, White, Green Component 2- 22 AWG/2 ISP TC Insulation - Polypropylene .046 Nominal Shielding - Aluminum Mylar with drain Color Code - Brown/Orange, Blue/Yellow	Standard Reels 1,000', 2,500', 5,000' Other lengths available. Please consult your factory representa- tive for availability.

PART NO.	COMPONENTS		OUTER JKT THICKNESS		ЛINAL).D.	WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
9928F	3	.020 PVC	.508 PVC	.344 x .688	8.74 x 17.47	113



VIDEO DETECTION CABLE

Composite Camera Cable





Specifications CoaxSpecifications Multi-ConductorsPut-UpsConductor - 20 AWG Sol BC .032Component 1- 16 AWG/3c BCStandard ReelsBraid - 2 x 98% TCInsulation - PVC .030 Nominal1,000', 2,500', 5,000'Jacket - LDPE .304 NominalJacket - PVC .030 NominalOther lengths available. Please consult your factory representative for availability.

Cable Identification

Ink jet print on jacket "ADVANCED DIGITAL CABLE, INC. 16-3C W/PRECISION VIDEO SUN RES DIR BUR MADE IN THE USA"

PART NO.	Components	OUTER JKT THICKNESS		NOMINAL OD		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
99163SFX	2	.030 PVC	.762 PVC	.395 x .700	10.03 x 17.78	143

Composite Camera Cable





Specifications Coax	Specifications Multi-Conductors	Put-Ups
Conductor - 20 AWG Sol BC .032 Braid - 95% BC Jacket - PVC .224 Nominal	Component 1- 18 AWG/5c BC Insulation - PVC (PVC Nylon 600V Available Upon Request) Color Code - White, Black, Red, Brown, Blue	Standard Reels 1,000', 2,500', 5,000' Other lengths available. Please consult your factory representa- tive for availability.

Cable Identification

Ink jet print on jacket "ADVANCED DIGITAL CABLE, INC. RG 59/U + 18/5 (UL) TYPE CM OR c(UL) CM E179333

PART NO.	Components	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
9915	2	.030 PVC	.762 PVC	.395 x .700	10.03 x 17.78	115

The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable. ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice.

