

1. CONDUCTOR:

- 1.1 Size and Material: 14 7/.0242" AWG tin-plated copper wire.
- 1.2 O.D.: .071" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on insulation: "E76475 (>R)U AWM 3071 600V 200°C HBR-F (UL) SF-2 CSA SEW-2 FT1 600V 200°C"
- 2.3 Covering: braided fiberglass yarn impregnated with a saturant to minimize fraying.
- 2.4 O.D.: .131" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C
- 3.3 Flame test rating: UL VW-1 / CSA FT1

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3071.
- 4.2 UL Standard 66 (Fixture Wire), Type SF-2.
- 4.3 CSA Standard C22.2 No. 127 (Equipment and Lead Wires), Type SEW-2.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.		Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
										Date: October 16, 2020				
										Verified: <i>Camille Lefebvre</i>				
										Date: October 16, 2020		Description: XSR30Z147/0242GB-X		
										Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F00970-X
UNCONTROLLED DOCUMENT A later revision of this specification may exist.														