

Technical Data Sheet



CERTIFICATIONS



ROHRFLEX MULTI PA 6



Corrugated all-plastic tubing, internally and externally corrugated. Ideal for static applications with large quantities of cables.

Material: Plastics PA 6

Temperature:

-40°F ... +248°F

-40°C ... +120°C

Flammability: HB [UL 94]

Aerosusa.com
service@aerosusa.com
717-200-7151

Technical Data Sheet

Product #	Profile	Color	Trade Size	AD	ID x OD (in)	Stat BR (in)	Dyn BR (in)	lb/ft	PU
1206.202.056	Fine	Black	2"	56	2.21 x 2.64	5.12	10.63	0.3091	32 FT
1206.202.070	Fine	Black	3"	70	2.61 x 3.11	6.69	13.78	0.3360	32 FT
1206.202.095	Fine	Black	4"	95	3.58 x 4.17	8.86	17.72	0.6384	32 FT
1206.201.070	Fine	Grey	3"	70	2.61 x 3.11	6.69	13.78	0.3360	32 FT
1206.201.095	Fine	Grey	4"	95	3.58 x 4.17	8.86	17.72	0.6384	32 FT

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
 Harrisburg, PA 17103