

1. CONDUCTOR:

- 1.1 Size and Material: 16 7/.0192" AWG tin-plated copper wire.
- 1.2 O.D.: .058" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on insulation: as per UL Standard.
- 2.3 Covering: braided fiberglass yarn impregnated with a saturant to minimize fraying.
- 2.4 O.D.: .133" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C
- 3.3 Flame rating: VW-1 (UL) / Horizontal flame (UL).

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3071.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.

UNCONTROLLED DOCUMENT

A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

Done:

Daniel Curson

Date:

July 27, 2021

Verified:

David Lott

Date:

July 27, 2021

Size:

A

Scale:

Page:

1 of 1

Code Ident. No:

57104

Specification No.:

F03031-X

Rev.



Harbour
INDUSTRIES

1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com

Description:

XSR30Z167/0192GB-X