







Standard Relay Rack HPW84RR19

### **Specifications**



- Rack material: extruded aluminum
- Black powder coated or mill finish
- Weight capacity: 1,000lb bolted to floor; 500lb unsecured
- Supports 19" EIA wide rack-mount equipment
- #12-24 threaded holes
- Rack unit numbered

## Standards

- UL 1863
- EIA/ECA-310-E Universal Mounting Pattern

# 3" Deep Relay Racks

n I	ch rack unit numbered	A.4 1: \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	F	D il D il	
Rack Units	External Height Inches (mm)	Mounting Width Inches (mm)	External Width Inches (mm)	Rail Depth Inches (mm)	Catalog No.
24	47" (1194)	19" (483)	20" (514)	3" (76)	HPW48RR19*
36	67" (1702)	19" (483)	20" (514)	3" (76)	HPW66RR19*
45	84" (2134)	19" (483)	20" (514)	3" (76)	HPW84RR19*
		23" (584)	20" (514)	3" (76)	HPW84RR23
48	89" (2261)	19" (483)	20" (514)	3" (76)	HPW90RR19
51	95" (2413)	19" (483)	20" (514)	3" (76)	HPW96RR19

<sup>\*</sup>Standard finish is Black; add **ML** to Catalog Number for Mill Finish



Rack with Vertical Cable Managers CS1976H



Z-Channel Manager, Hinged

### **Specifications**

- Rack material: extruded aluminum
- Black powder coated
- Weight capacity: 1,000lb bolted to floor; 500lb unsecured
- Supports 19" EIA wide rack-mount equipment
- #12-24 threaded holes
- Rack unit numbered

### **Standards**

- UL 1863
- EIA/ECA-310-E Universal Mounting Pattern

## 3" Deep Relay Racks with Cable Managers

Rack	External Height	External Width	Rail Depth	Z Width		
Units	Inches (mm)	Inches (mm)	Inches (mm)	Inches (mm)	Cover Style	Catalog No.
45	84" (2134)	19" (483)	3" (76)	3" (152)	Hinged	CS1973H
					Clip On	CS1973
				6" (152)	Hinged	CS1976H
					Clip On	CS1976