

Heatshrinkable Moulded Shapes Bulbous Straight Boots HellermannTyton

DRAWING No.
152086

SHT. 1
OF
1 SHTS.

© THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HELLERMANN TYTON. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF HELLERMANN TYTON.

THIRD ANGLE PROJECTION

BS 8888

DO NOT SCALE
IF IN DOUBT ASK

Q.A.

H/S Q.A.

H/S PROD

H/S SETT

REL. INSP.

EXT.ISS.CODE

5/12

STANDARD PART (AFTER UNRESTRICTED RECOVERY)

EXPANDED (AS SUPPLIED)

DRAWING OFFICE TO NOTIFY
DATABASE ADMINISTRATOR TO
UPDATE
PART NUMBER IF DRAWING
IS UP ISSUED.

SPEC.	PART No.	EXPANDED DIAMETERS (AS SUPPLIED)		RECOVERED DIAMETERS		RECOVERED DIMENSIONS						
		øh	øj	øH	øJ	P	R	S	T	V	Hw	Jw
		MIN	MIN	MAX	MAX	±10%	NOM	NOM	±20%	MAX	±20%	±30%
—	155-12	36 (1.42)	36 (1.42)	18 (0.71)	7 (0.28)	67 (2.64)	35 (1.38)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
VG 95343 T06A004A	155-41	31 (1.22)	31 (1.22)	18 (0.71)	7 (0.28)	47 (1.85)	15 (0.59)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
VG 95343 T06B004A	155-42	31 (1.22)	31 (1.22)	18 (0.71)	7 (0.28)	67 (2.64)	35 (1.38)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
—	155-51	29.2 (1.15)	15 (0.59)	18 (0.71)	7.3 (0.29)	47 (1.85)	15 (0.59)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
—	155-52	29.2 (1.15)	15 (0.59)	18 (0.71)	7.3 (0.29)	67 (2.64)	35 (1.38)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
—	155-53	31 (1.22)	18 (0.71)	18 (0.71)	7.3 (0.29)	67 (2.64)	35 (1.38)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
VG 95343 T29A004A	155-61	31 (1.22)	18 (0.71)	18 (0.71)	7 (0.28)	47 (1.85)	15 (0.59)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)
VG 95343 T29B004A	155-62	31 (1.22)	18 (0.71)	18 (0.71)	7 (0.28)	67 (2.64)	35 (1.38)	18 (0.71)	1.0 (0.04)	3.3 (0.13)	1.8 (0.07)	1.0 (0.04)

OPTIONAL FILLER PORT DETAIL			
SPEC.	PART No.	RECOVERED DIMENSIONS	
		X	Y
		±20%	±20%
—	155-12	25 (0.98)	32 (1.26)
VG 95343 T07A004A	155-41	12 (0.47)	25 (0.98)
VG 95343 T07B004A	155-42	25 (0.98)	32 (1.26)
—	155-51	12 (0.47)	25 (0.98)
—	155-52	25 (0.98)	32 (1.26)
—	155-53	25 (0.98)	32 (1.26)
—	155-61	12 (0.47)	25 (0.98)
—	155-62	25 (0.98)	32 (1.26)

OPTION TO STANDARD PART
FILLER PORT (CODE P)

1 FILLER PORT
ø4.5 NOM (0.18)

1 DRAIN HOLE
ø3.0 NOM (0.12)

Heatshrinkable Moulded Shapes Bulbous Straight Boots HellermannTyton

6
5
4
3
2

P1499
P1466
P1399
P1362
P1329

GL
CB
CM
DJC
G.B.

24/02/15
03/07/14
03/01/13
05/10/11
11/10/10

HellermannTyton

William Prance Road,
Plymouth International Med. & Tech. Park,
Plymouth, PL6 5WR
Tel ++44 (0) 1752 701261
Fax ++44 (0) 1752 790058

NAME
DATE
TITLE

S.Almond
14/04/08
BOTTLE SLEEVE

SCALE
DIMS IN

NTS
mm (in)

ADHESIVE

PART No.
155

DRAWING No.
152086

SHT. 1
OF
1 SHTS.

For information only, not subject to technical changes.