4/4C Type SOOW Black



PRODUCT DATA SHEET

SOOW portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavy-duty cable service applications. This cable is rated to 600 volts and has a temperature range of - 40° C to $+90^{\circ}$ C. These characteristics make SOOW portable cord an excellent choice for mitigating outdoor factors.

Design Number10046Part Number32104522Customer NumberN/A

CONSTRUCTION

Conductor: Stranded bare copper, Class H per ASTM B-173

Conductor Size: 4AWG(133/25) **Separator:** Polyester tape **Insulation:** EPDM, oil resistant

Insulation Avg. Thickness: 0.060" (Nom.) Insulated Conductor **0.D**: 0.386" (Nom.)

Filler: Jute rope

Separator: Non woven cloth

Jacket Material: CPE, oil resistant


Jacket Avg. Thickness: 0.155" (Nom.)

Overall Diameter: 1.250" (Nom.)

Jacket Color: Black

Print Legend:

ASCENT E486041 4AWG 4/C SOOW (UL) 600V (-40C-90C)--CSA LL268042 FT-2 WATER RESISTANT P-07KA140001-MSHA--RoHS xxxxxFT



Color Code: Black, White, Red, Green

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +90°C

Operating Voltage: 600V **Flame Test:** CSA FT2

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL Flexible Cord, Subject 62
CSA Flexible Cord, C22.2 No.49
MSHA Approved

Application: Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2019/07/16	Initial release
01	2020/03/03	Unify the print legend format same as SJ00W series
Created L. Jian		Approved A. Huang



