## 16/6C Type SOOW Black



PRODUCT DATA SHEET

SOOW portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavy-duty cable service applications. This cable is rated to 600 volts and has a temperature range of -  $40^{\circ}$ C to  $+90^{\circ}$ C. These characteristics make SOOW portable cord an excellent choice for mitigating outdoor factors.

Design Number10107Part Number32109658Customer NumberN/A

## **CONSTRUCTION**

Conductor: Stranded bare copper, Class K per ASTM B-174

**Conductor Size:** 16AWG(26/30) **Insulation:** EPDM, oil resistant

Insulation Avg. Thickness: 0.030"(Nom.)
Insulated Conductor **0.D:** 0.124"(Nom.)

Filler: Cotton

Separator: Non woven cloth

Jacket Material: CPE, oil resistant

Jacket Avg. Thickness: 0.080" (Nom.)


Jacket Color: Black

**Overall Diameter:** 0.528"(Nom.)

**Print Legend:** 

Ascent E486041 16AWG 6C SOOW UL 600V (-40C-90C) CSA LL268042 FT-2

Water Resistant P-07KA140001 MSHA -RoHS xxxxxFT



Color Code: Black, White, Red, Green, Orange, Blue

## **ELECTRICAL CHARACTERISTICS**

**Operating Temperature (°C):** -40°C to +90°C

**Operating Voltage:** 600V **Flame Test:** CSA FT2

## SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL Flexible Cord, Subject 62
CSA Flexible Cord, C22.2 No.49
MSHA Approved

**Application:** Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

		Revision History	
00	2019/08/01	Initial release	
Created L. Jian		Approved A. Huang	-

