PRODUCT SPECIFICATION

DESCRIPTION **DATE** REV **ECN** 10/13/2015 Updated low temp info.

Parent Number: F1406712E7

Description: 14 41/30 TC MTW or BC-5W2 or THHW or

AWM 1011/1015/1230/1335 or 1032 TEW or TOLERANCE ±: +0.003/-0.002

AWM I A/B OD 0.140" MGN/YEL-D

DIAMETER: 0.140

Stranding: 41/30 TC LHL

<u>Style:</u> <u>UL: MTW or BC-5W2 or THHW or AWM 1011/1015/1230/1335</u> or 1032 CSA: TEW or AWM I A/B

MIN AVG WALL: 0.030

MINIMUM WALL: 0.027

Insulation: PVC

Print Legend: 14 AWG (2.08mm2) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW FLEXING OR THHW OR AWM 1011/1015/1230/1335 600V OR 1032 1000V MOISTURE RESISTANT VW-1 -- 156205 CSATEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V, 1032=1000V

Temperature: 1011=80C, 1015=105C, 1032=90C, 1230: DRY=105C WET=60C, MTW/1335: DRY=90C WET=60C, BC-5W2: DRY=105C

WET=75C, THHW: DRY=90C WET=75C, TEW/AWM I A/B=105C

Notes: 1. Min Temp: -40C

2. CSA TEW: -30C

3. Stripe Coverage: Euro Stripe - 35±5% coverage at 1 location

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Title: _____Company Name: ____ Southwire'

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115