

For more Information  
please call

1-800-Belden1



## General Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

## Physical Characteristics (Overall)

### Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 1            | 20  | 10x30     | TC - Tinned Copper |

Total Number of Conductors: 1

### Insulation

Insulation Material:

| Insulation Material      | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | .030                 |

### Overall Insulation

#### Overall Cable

Overall Nominal Diameter: 0.100 in.

## Mechanical Characteristics (Overall)

Bulk Cable Weight: 7.500 lbs/1000 ft.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

UL Rating: 600 V, 105°C

UL Type: MTW or AWM 1015/1230

CSA Rating: 600 V, 105°C

CSA Type: AWM I A/B or TEW

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

### Flame Test

UL Flame Test: VW-1

CSA Flame Test: FT1

### Plenum/Non-Plenum

Plenum (Y/N): No

## Put Ups and Colors:

| Item #       | Putup    | Ship Weight | Color  | Notes | Item Desc      |
|--------------|----------|-------------|--------|-------|----------------|
| 8919 0011000 | 1,000 FT | 8.000 LB    | BROWN  | P     | 20 STR PVC BRN |
| 8919 002100  | 100 FT   | 0.900 LB    | RED    |       | 20 STR PVC RED |
| 8919 0021000 | 1,000 FT | 8.000 LB    | RED    | P     | 20 STR PVC RED |
| 8919 0031000 | 1,000 FT | 8.000 LB    | ORANGE | P     | 20 STR PVC ORG |

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 8919 Hook-up/Lead - UL AWM Style 1015

|              |          |           |             |   |                   |
|--------------|----------|-----------|-------------|---|-------------------|
| 8919 004100  | 100 FT   | 0.900 LB  | YELLOW      |   | 20 STR PVC YEL    |
| 8919 0041000 | 1,000 FT | 8.000 LB  | YELLOW      | P | 20 STR PVC YEL    |
| 8919 005100  | 100 FT   | 0.900 LB  | GREEN, DARK |   | 20 STR PVC GRN    |
| 8919 0051000 | 1,000 FT | 8.000 LB  | GREEN, DARK | P | 20 STR PVC GRN    |
| 8919 0081000 | 1,000 FT | 8.000 LB  | GRAY        | P | #20 STR PVC GRY   |
| 8919 009100  | 100 FT   | 0.900 LB  | WHITE       |   | 20 STR PVC WHT    |
| 8919 0091000 | 1,000 FT | 8.000 LB  | WHITE       | P | 20 STR PVC WHT    |
| 8919 010100  | 100 FT   | 0.900 LB  | BLACK       |   | 20 STR PVC BLK    |
| 8919 0101000 | 1,000 FT | 8.000 LB  | BLACK       | P | 20 STR PVC BLK    |
| 8919 0105000 | 5,000 FT | 40.000 LB | BLACK       | C | #20 STR PVC BLK   |
| 8919 013100  | 100 FT   | 0.900 LB  | BLUE, DARK  |   | 20 STR PVC DK.BLU |
| 8919 0131000 | 1,000 FT | 8.000 LB  | BLUE, DARK  | P | 20 STR PVC DK.BLU |
| 8919 0135000 | 5,000 FT | 40.000 LB | BLUE, DARK  | P | 20 STR PVC DBLU   |

**Notes:**

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2    Revision Date: 08-26-2008

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.