



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#24 19/36 TINNED COPPER .010" PVC RoHS COMPLIANT

24 AWG E25635 RU AWM STYLE 10002 105c – 300v OR
AWM STYLE 1061 80c - 300v VW-1 CSA 150272 AWM I-A/B 80c - 300v FT1 S-R
PVC

CONDUCTOR:	#24 19/36 TINNED COPPER 3/8" UNILAY NOMINAL O.D.	.024"
	APPROXIMATE CIRCULAR MILL AREA	475
	WEIGHT PER THOUSAND FEET	1.50#
	BASIC SPECIFICATION	ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	300v
	ELONGATION	300% AVE
	TENSILE STRENGTH	3210 PSI AVE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	60 (D)
	OXYGEN INDEX	28
	BRITTLE POINT	-8c
	SPARK TESTED	5,700 VOLTS
	FINISHED O.D.	.044"
	WEIGHT PER THOUSAND FEET	2.14#
USE:	INTERNAL WIRING OF ELECTRIC BOOKEEPING, ACCOUNTING, TIME RECORDING MACHINES OR ELECTRONIC EQUIPMENT IF WITHIN A CHASSIS OR PROTECTED FROM MECHANICAL INJURY.	

Info@atlaswirecorp.com

Revision 10-18-16