

Technical data sheet

PUR control cables · C-track compatible · unshielded

LUTZE SUPERFLEX® PLUS 3000 PUR

For highest requirements



Identification

Type

SU+ 3000 PUR 7G0,5

Part No.

[113036](#)

Product version

Datasheet version

02

Use/Application/Properties

- Application
- Machine and device construction, transport and conveyor technology, heating and climate technology
 - In areas with high concentrations of people or material assets, where corrosive gases need to be avoided in the event of fire
 - As a monitoring, measurement and control cable for industrial applications
 - Especially for harsh environments
 - For installation in energy chains with constant linear movement
- Properties
- Reduced friction due to very smooth conductor insulation (HGI) for high mechanical loads
 - Low capacitance, very good electrical properties
 - Flame-retardant, self-extinguishing
 - Very good alternating bending strength
 - Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
 - Hydrolysis-resistant, microbe-resistant, and rot-resistant
 - Weathering, ozone and UV resistant (normal lighting conditions)
 - Industrial and salt water resistant
 - Excellent coolant and lubricant resistance
 - Largely resistant to oils, greases, alcohol-free benzines and kerosene
 - Silicone free

Construction

Description

SUPERFLEX® PLUS 3000 PUR

Number of conductors/cross-section

7G0,5

Number of conductors

7

Cross-section, metric

0.5 mm²

Jacket material

PUR

Jacket color

grey similar to RAL 7001

Outer Ø

6.7 mm

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

Technical data sheet

PUR control cables · C-track compatible · unshielded

Weight	6.48 kg/100 m
Weight	43.42 Lbs/Mft
Cu Index	3.4 kg/100 m

Construction Element 1

Element construction	7G0,5
Conductor	CU-wire bare
Conductor category	DIN EN 60228, class 6 IEC 60228, Class 6 DIN EN 13602
Conductor marking	black · with white number print · green/yellow
Conductor insulation	TPE
Cabling	conductors layered construction conductors twisted without mechanical stress layer pitch optimised

Overall construction

Overall stranding	conductors layered construction conductors twisted without mechanical stress layer pitch optimised
-------------------	--

Technical data

Rated voltage U ₀ /U	300/500 V
Rated voltage UL	300 V
Test voltage type	2000 V
Temperature range moving	-25 °C ... +90 °C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius moving	7.5×cable OD
Minimum bending radius fixed	4×cable OD
Bending cycles	≥10 Mio
Speed	5 m/s
Acceleration	10 m/s ²
Torsion cycles	≥ 1 Mio
Torsion	± 60°/m
Speed of torsion	60 °/s
Acceleration of torsion	30 °/s ²

Technical Data Element 1

Element construction	7G0,5
Insulation resistance at 20 °C	100 MΩ×km
Conductor resistance	39 Ω/km
Operating capacitance wire-wire	56 pF/m

Approvals/Standards

Approvals	cURus
-----------	-------

Technical data sheet

PUR control cables · C-track compatible · unshielded

UL style	AWM 21209
Conformity	CE RoHS REACH
Burning behavior according to	VDE 0482-332-1-2 DIN EN 60332-1-2 IEC 60332-1 UL 1581 part VW-1 Flame Test CSA FT 1
Oil resistant according to	Oil Res II
Halogen free according to	IEC 60754-1 DIN EN 60754-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--