

For more Information  
please call

1-800-Belden1



### General Description:

12 AWG solid .086" bare copper conductor, foam polyethylene insulation, Duobond IV® quad shield (100% coverage), PVC jacket.

### Usage (Overall)

Suitable Applications: Thick Ethernet

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	12	Solid	BC - Bare Copper	2.1844

Total Number of Conductors: 1

#### Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FPE - Foam Polyethylene	6.1722

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	94
3	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
4		Braid	TC - Tinned Copper	90

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 10.287 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +60°C
UL Temperature Rating:	60°C (UL AWM Style 1478)
Bulk Cable Weight:	181.560 Kg/Km
Max. Recommended Pulling Tension:	1134.291 N
Min. Bend Radius/Minor Axis:	107.950 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CL2, CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 1478 (30 V 60°C)
EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	IEEE802.3 10Base5
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

## METRIC MEASUREMENT VERSION

## 9880 Coax - Coaxial Cable - Thicknet 10Base5 Ethernet

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-00451-00

### Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	89880

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
50	+/- 2

### Nom. Inductance:

Inductance (µH/m)
0.213265

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
85.306

### Nominal Velocity of Propagation:

VP (%)
78

### Nominal Delay:

Delay (ns/m)
4.2653

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
4.65902

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
4.98712

### Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	0.62339
5	1.21397
10	1.70612
50	3.9372
100	5.5777
200	8.36655
400	12.7959
700	18.0455
900	21.3265
1000	22.6389
1500	27.8885
2000	33.1381
2500	37.7315
3000	42.653

### Max. Operating Voltage - UL:

Voltage	Description
300 V RMS	
30 V RMS	UL AWM 1478

## Notes (Overall)

**Notes:** Ringband stripes every 2.5 meters to aid users in tap placement.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9880 0041000	1,000 FT	131.000 LB	YELLOW	C	11H 50 OHM TRUNK CABLE
9880 0041640	1,640 FT	219.760 LB	YELLOW	C	11H 50 OHM TRUNK CABLE

## METRIC MEASUREMENT VERSION

### 9880 Coax - Coaxial Cable - Thicknet 10Base5 Ethernet

9880 004500	500 FT	66.000 LB	YELLOW	C	11H 50 OHM TRUNK CABLE
-------------	--------	-----------	--------	---	------------------------

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 09-25-2012

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.