




ATLAS WIRE CORP

1601 Glenlake Ave. Itasca, IL 60143
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



SPECIFICATION SHEET


Atlas Part #: 1401B3173

Description: #14 SOLID BC 1/32" XLPE UL 3173

A - CONDUCTOR: #14 SOLID BARE COPPER

A1	NOMINAL O.D.	0.0641
	STANDARD	ASTM B 3

B - INSULATION:	MATERIAL	XLPE
	TEMPERATURE RATING	125c
	VOLTAGE RATING	600v
	ELONGATION	425% AVERAGE
	TENSILE STRENGTH	2,300 PSI AVERAGE
B1	WALL THICKNESS (APPROX)	0.031"
B2	INSULATED O.D. (APPROX)	0.127"



PRODUCT WEIGHT: WEIGHT / THOUSAND FEET (APPROX) 17 lbs.

REGULATORY COMPLIANCES REACH, RoHS, UL, CSA

PRINT LEGEND 14 AWG. E25635 RU AWM STYLE 3173 125C - 600V X-LINK SUITABLE FOR "SWITCHBOARD WIRE" IN THE UNITED STATES CSA 150272 CL1251 OR AWM I - A/B 125C 600V FT-2

IMPORTANT:

All measurements are nominal, comply with applicable standards, and are subject to change. We make every reasonable effort to ensure data is current and accurate but there may be errors or omissions. It is the user's responsibility to ensure the product is relevant to their applicable usage, and according to their local codes. The sale of this product is subject to Atlas Wire LLC's standard terms and conditions.