


PROPRIETARY INFORMATION, DO NOT REPRODUCE WITHOUT WRITTEN APPROVAL FROM RSCC AEROSPACE & DEFENSE. Information contained in this drawing may be subject to U.S. export control laws and regulations, such as the U.S. International Traffic in Arms Regulations or the Export Administration Act. The receiving Party agrees that information subject to the export control laws and regulations shall not be disclosed or transferred (such as for example disclosure or transfer to a foreign national whether within or outside the U.S., or disclosure or transfer to a foreign country) except in compliance with all applicable U.S. export control laws and regulations.

Product Type:
Ground Support
Custom Cable

Drawing Number
DN-20423



- 1.0 CONDUCTOR** 16AWG 19/29 Tin Coated Copper - .053" Nom.
- 2.0 INSULATION** Irradiation Cross-linked Polyalkene - .0065" Wall Nom
Covering: Irradiation Crosslinked PVDF - .003" Wall Nom
- 3.0 TWIST** Two (2) of the above singles. - .144" OD Nom
- 4.0 CABLE** Two (2) Twisted Pair Components with Drain Wire - .252" OD Nom
Drain Wire: 16AWG 19/29 Tin Coated Copper
- 5.0 TAPE** Aluminum/Polyester Tape. 50% Nom Lap
- 6.0 JACKET** Irradiation Cross-linked PVDF (White) - .010" Nom. Wall
- 7.0 DIAMETER** .276" ± .010"
- 8.0 IDENTIFICATION** Components: (I) White, Green; (II) Black, Red
Jacket Print: **RSCC AEROSPACE & DEFENSE DN-20423**

Customer:	Drawn By: L Roper	Approved By: K Coderre	Revision: 1	Date: 01-09-13
Changes	Made By:	Approved By:	Revision:	Date:
CARLOS LAMAROS				
Edg. upg. CVA Mexico				