

## **Specification Canfield W1101**

**US North Central** 

5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date:

4/12/2013

Issue:

1

## Construction

Description	1: 3 Cond 18 (16) BC P	3 Cond 18 (16) BC PVC/PUR			Diam. (In)
Component:	3 Conductors				0.048"
Conductor:	18 16/30 BC to ASTN	18 16/30 BC to ASTM B 174-71			
Insulation:	0.015" Prem	ium Grade PVC			0.078"
	Cong Cong	Color C	Color On 3 Yellow/Green	Color	9
Cable Assembly:	3 Conductors Bunched Cabled				0.1677"
Jacket:	0.037 Pressu	0.037 Pressure PUR Polyurethane Apply Talc when Jacketing			
Jacket Color:	Black Jacket with whit	e print			0.235"
Print: E174416 RU AWM-20233 80C 300V VW-1 cRU AWM I/II A/B 80C 300V FT-1 CANFIELD CONNECTOR W1101 18/3 PUR					
Specifications:					
UL Canadian cUL Bend Radius	AWM - 20233 AWM I/II A/B 1.62"	708 708	300 Volt 300 Volt	VW-1 FT-1	
Bena Radius	1.02				
t	002/95/EC(RoHS): All materials used in the manushe restriction of use of certain				
REACH Regulation (EC 1907/2006):					
This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.  California Prop 65:					
	Γhe outer surface materials u	sed in the manuf	acture of this part meet the	ne requirements o	f California Prop. 65.

**APPROVED** 

MA 4/15/2013