

Specification Canfield W1083

US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date:

12/4/2014

Issue:

-

Construction

Description	on: 3 Cond 18 (16) i	3 Cond 18 (16) BC PVC/PUR			Diam. (In)
Component:	3 Conductors				
Conductor:	18 16/30 BC to	18 16/30 BC to ASTM B 174-71			0.048"
Insulation:	0.015"	Premium Grade PVC			0.080"
Color Code		Color Co	Color Cond	Color	
	1 Black	2 Green	3 White		
Cable Assembly:	3 Conductors Bu	nched Cabled			0.1677"
Jacket:	0.045 E	Black Matte Finish PVC	Talc Only No Sepa	rator	0.275"
Jacket Color: Black Jacket with white print					0.275"
Print: E174416 RU AWM-2464 80C 300V VW-1 cRU AWM I/II A 80C 300V FT1 CANFIELD CONNECTOR W1083 18/3					
Specifications:					
UL	AWM - 2464	208	300 Volt	VW-1	
Canadian cUL	AWM I/II A	208	300 Volt	FT-1	
Bend Radius	2.2"				

Environmental Compliance

EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.

Tred G. Milleefe.