

## Unshielded Multi-Conductor FT-4



1-888-Electro

Fax 613-394-4101

SALES @ ELECTROCABLES.COM

Stranded Tinned Copper Conductors\*  
 SR-PVC Insulation, Grey PVC Jacket FT-4  
 -20° C to 105° C, Contact [sales@electrocables.com](mailto:sales@electrocables.com) for approval info

[Home](#)  
[Electronic & Electrical Index](#)  
[Search](#)  
[Previous](#)   [Next](#)  
 Colour Code: ECI Chart 1

| ECI<br>Catalogue<br>Number | Conductor |             |           | Wall Thickness         |                    | Nominal<br>O.D.<br>(inches) | Total<br>Weight<br>(lbs/km) | Colour Code |
|----------------------------|-----------|-------------|-----------|------------------------|--------------------|-----------------------------|-----------------------------|-------------|
|                            | No.       | AWG<br>Size | Stranding | Insulation<br>(inches) | Jacket<br>(inches) |                             |                             |             |
| 6102007TFT4                | 7         | 20          | 7 x 28    | .010                   | .023               | .225                        | 153                         | ECI Chart 1 |
| 6102009TFT4                | 9         | 20          | 7 x 28    | .010                   | .023               | .249                        | 187                         | 1           |
| 6102010TFT4                | 10        | 20          | 7 x 28    | .010                   | .023               | .264                        | 208                         | 1           |
| 6102012TFT4                | 12        | 20          | 7 x 28    | .010                   | .023               | .279                        | 233                         | 1           |
| 6102015TFT4                | 15        | 20          | 7 x 28    | .010                   | .030               | .306                        | 305                         | 2           |
| 6102019TFT4                | 19        | 20          | 7 x 28    | .010                   | .030               | .338                        | 374                         | 2           |
| 6102025TFT4                | 25        | 20          | 7 x 28    | .010                   | .030               | .380                        | 478                         | 2           |
| 6101851TFT4                | 2         | 18          | 16 x 30   | .012                   | .020               | .195                        | 87                          | Black/Red   |
| 6101803TFT4                | 3         | 18          | 16 x 30   | .012                   | .023               | .207                        | 113                         | 1           |
| 6101804TFT4                | 4         | 18          | 16 x 30   | .012                   | .023               | .226                        | 147                         | 1           |
| 6101805TFT4                | 5         | 18          | 16 x 30   | .012                   | .023               | .237                        | 167                         | 1           |
| 6101806TFT4                | 6         | 18          | 16 x 30   | .012                   | .023               | .255                        | 193                         | 1           |
| 6101807TFT4                | 7         | 18          | 16 x 30   | .012                   | .023               | .271                        | 220                         | 1           |
| 6101808TFT4                | 8         | 18          | 16 x 30   | .012                   | .023               | .286                        | 246                         | 1           |
| 6101809TFT4                | 9         | 18          | 16 x 30   | .012                   | .023               | .300                        | 273                         | 1           |
| 6101812TFT4                | 12        | 18          | 16 x 30   | .012                   | .030               | .353                        | 360                         | 2           |
| 6101815TFT4                | 15        | 18          | 16 x 30   | .012                   | .030               | .386                        | 440                         | 2           |
| 6101819TFT4                | 19        | 18          | 16 x 30   | .012                   | .030               | .429                        | 547                         | 2           |
| 6101825TFT4                | 25        | 18          | 16 x 30   | .012                   | .035               | .485                        | 686                         | 2           |
| 6101830TFT4                | 30        | 18          | 16 x 30   | .012                   | .035               | .524                        | 809                         | 2           |
| 6101840TFT4                | 40        | 18          | 16 x 30   | .012                   | .050               | .633                        | 1147                        | 2           |

*\*Stranded bare copper conductors and special packaging and colours available upon request.  
 Aluminum or Steel Interlock Armour and Jacket available upon request.*

This web site was last modified on Jul. 30, 2009 , ISO 9001:2000, Rev.58 All Rights Reserved.