



DECA CABLES INC.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

PRODUCT DATA SHEET

PART NUMBER	73-406
DESCRIPTION	AWM 6/C 18 AWG SHIELDED FT4 105C
CONDUCTOR	18 AWG TINNED COPPER
STRANDING	16 x 0.010"
CONDUCTOR DIAMETER	0.047"
RESISTANCE	7.15 OHMS/1000FT
INSULATION	SR PVC
INSULATION THICKNESS	0.012"
INSUL. COND. DIAMETER	0.072"
CAPACITANCE	29 PF/FT
SHIELD	ALUMINUM/MYLAR TAPE
DRAIN	22 AWG 7 x 0.010" TINNED COPPER
RIPCORD	POLYESTER RIPCORD UNDER JACKET
JACKET	PVC
JACKET THICKNESS	0.023"
FINISHED DIAMETER	0.277"
CSA CERTIFIED	CMG, AWM II
UL RECOGNIZED	CM
FLAME RATING	FT4

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.