


REV.	DESCRIPTION	DATE
0	Preliminary Release	8/27/2021
1	Initial Release	8/8/2024



Color Code	
-001	Black

Item	Component	Description	Thickness				Dimensions					
			D	inch		mm		D	inch		mm	
				Nom	Min	Nom	Min		Nom	Tol	Nom	Tol
1.	Conductor:	0.35mm2 7/.25mm Bare Copper						0.028		0.71	NA	
2.	Insulation:	EXRAD 150UT XLPE		0.013	0.011	0.32	0.28	<D>	0.053	0.002	1.35	0.05

General Data:

Insulation Resistance >100MQ-KM

Conductor Resistance: 54.4 mohms /m max. at 20C

Spark test Voltage 6000 Volts

Voltage Rating 600 VAC/900VDC per 19642-5

Meets Requirements of ISO 6722-1, ISO 19642-5, Class D Thin Wall

Temperature Range: -40° C to +150° C

Weight 3.00 lbs./1000 Feet

min Static Bend Radius inches mm

0.2 4

	0.35mm2 EXTRAD 150UT 600 Volt Wire lead Wire										
	DRN. Richard Antic				DATE 8/27/2021						
	CKD. R. Trahan				DATE 7/10/2024						
DO NOT SCALE THIS DRAWING	SIZE A		PART NUMBER 15-09074			DOCUMENT NUMBER 18955					
The information on this drawing is the proprietary property of Champlain Cable Corporation, and may not be used, reproduced or disclosed to others, in whole or in part, without written authorization.											PAGE 1 of 1