



HOOK-UP WIRE



MIL-W-16878/4

TYPE E-600V

**Description:**

Stranded Silver Plated Copper, Extruded PTFE Insulation

Characteristics:

Temperature Rating:

MIL-W-16878: -60°C to +200°C

UL 1213: +105°C

Voltage Rating:

MIL-W-16878:600V

UL 1213: Not Rated Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2132	M16878/4BAB-X	32	7/40	.010	.030
2130	M16878/4BBB-X	30	7/38	.010	.032
2128	M16878/4BCB-X	28	7/36	.010	.036
2128/19	M16878/4BCE-X	28	19/40	.010	.036
2126	M16878/4BDB-X	26	7/34	.010	.040
2126/19	M16878/4BDE-X	26	19/38	.010	.041
2124	M16878/4BEB-X	24	7/32	.010	.044
2124/19	M16878/4BEE-X	24	19/36	.010	.045
2122	M16878/4BFB-X	22	7/30	.010	.050
2122/19	M16878/4BFE-X	22	19/34	.010	.051

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2120	M16878/4BGB-X	20	7/28	.010	.058
2120/19	M16878/4BGE-X	20	19/32	.010	.059
2118	M16878/4BHB-X	18	7/26	.010	.068
2118/19	M16878/4BHE-X	18	19/30	.010	.070
2116/19 *	M16878/4BJE-X	16	19/29	.010	.077
2114/19 *	M16878/4BKE-X	14	19/27	.012	.094
2112/19 *	M16878/4BLE-X	12	19/25	.012	.113
2110/19 *	M16878/4BMG-X	10	37/26	.012	.134

NOTE: AWG 16-10 must be surface marked to comply with UL, please specify when ordering

*Not UL listed

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.