

## Specification C5352

US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 5/14/2014

Issue: 3

## Construction

Description:	on: 4 Cond 22 (7) TC SR-PVC/PVC AWM-2661 Cable					
Component:	4 Conduc	tors				•
Conductor:	22 7/30 T	22 7/30 TC to ASTM B 33-74				
Insulation:	0.01"	SR PVC				0.05"
Color Code:						
Coll		1 21		Color	Cond Color	]
1	Blue	2 E	Blue	3 Black	4 Black	
Assembly:	4 Conduc	0.121"				
Fillers	Fibrillated Polypropylene for roundness					0.121"
Tape:	Non-Woven Separator Tape for Strip-ability					0.124"
Jacket:	0.037"	0.037" AWM Jacket Compound				
Jacket Color:	Black					0.198"
Print: E174416 22/4 RU AWM STYLE 2661 VW-1 105C 300VCSA LL109360 AWM A/B I/II 105C 300V FT1 UV,OIL AND WATER RESISTANT						
Specifications:						
UL AW	M - 2661	105℃	300 Volt	VW-1		
Canadian CSA	AWM	105℃	300 Volt	FT-1	A/B I/II	
Environmental Com EU Directive 2002	•	8):				
All r	naterials used	l in the manufa	acture of this pa	rt are in complian	nce with EU Directive	2002/95/EU regarding

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65



## **US North Central**

5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 5/14/2014

Issue: 3

## Drawing/Rotation:

