

Specification

US North Central

5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 5/30/2013

Issue: 1

Construction

Description: 15 Cond 22(7) PVC/PVC OAFSB PVC								Diam. (In)
Component:	15 Conduc	ctors						
Conductor:	22 7/30 TC to ASTM B 33-74							0.03"
Insulation:	0.01"	0.01" Premium Grade PVC						
Color Code:								
	Cont. Color	Cond	Color	Cond	Color	Cond	Color	
	1 Black	2	Brown	3	Red	4	Orange]
	5 Yellow	6	Green	7	Blue	8	Violet	
	9 Slate	10	White	11	Wht/Blk	12	Wht/Brn	
	13 Wht/Red	14	Wht/Org	15	Wht/Yel			<u> </u>
Cable Assembly:								
Drain Wire:	Wire: 22 7/30 TC							
Shield: APA Aluminum Polyester Aluminum Foil Shield								0.238"
Shield: 70% Tinned Copper Braid Shield								0.259"
Jacket:								
Jacket Color:	acket Color: Gray							
Print:	E174416 RU AWM	1 2464 80C	300V VW-1 o	UR AV	WM IA 80C 30	00V R0	OHS	
Specifications:								
UL	AWM - 2464		90℃		300 Volt		VW-1	
			80℃		300 Volt			

Environmental Compliance

EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.