


US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323 www.IEWC.com

Issue Date:

10/18/2013

Issue:

Drawing/Rotation:



THE FLEXIBILITY OF THIS WIRE IS IMPORTANT TO THE SPECIFIC USER'S REQUIREMENTS. THE BENDING RADIUS SHOULD BE 8 TIMES OR LESS THE CABLE OUTSIDE DIAMETER. THIS RESULTS IN A BENDING RADIUS OF 1.34 INCHES OR LESS. THE MORE FLEXIBLE THE BETTER.

APPROVED

Mike Phillips 10/21/2013

MAAAAA



Specification

US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323 www.IEWC.com

Issue Date:

10/18/2013

Issue:

1

Construction

Description	on: 4 Cond 24	4 Cond 24(7) PVC/TPU Canfield W1184				
Component:	4 Conduct	ors	Taken Taken			Diam. (In)
Conductor:	onductor: 24 7/32 BC to ASTM B 8-77					0.024"
Insulation:	0.01"	Premiu	m Grade PVC			0.044"
Color Code:						
	Cond Color	1 Sall	Color	Color Color	Colo	
	1 Black		Green	3 White	4 Red	
Cable Assembly:	4 Conduct	ors Bunched	l Cabled			0.106"
Jacket:	0.03"	Polyure		0.106"		
Jacket Color:	Black					0.165"
Specifications: UL	AWM - 20233	208	300 Volt	VW-1		
Canadian cRU	AWM - I/II A	308	300 Volt	FT-1		
Environmental EU Directive	2002/95/EC(RoHS All materials used	in the manu			ance with EU Directi s in electrical and el	ve 2002/95/EU lectronic equipment.
REACH Regu	lation (EC 1907/20	06):				
California Pro	REACH candidate				rn (SVHC) listed on	the European Union's
		materials us	ed in the man	ufacture of this par	t meet the requirem	nents of California

APPROVED

M. Ke Phillips 10/21/2013

MM