


ÖLFLEX® POWER QUAD II

Oil-resistant PVC cordage with <HAR> & SJTO approvals for global use

LAPP KABEL STUTTGART ÖLFLEX® POWER QUAD II



ÖLFLEX® POWER QUAD II is a PVC cordage with UL/CSA SJTO and <HAR> H05VV-F approval. It has a very oil-resistant jacket and an international color code. ÖLFLEX® POWER QUAD II can be used in European, American, Asian, and Canadian cordage applications; one cable does the work of four.

Recommended applications

Power cordage for domestic machinery; portable tools; data processing; control systems; commercial appliances

Approvals



Cable attributes		page 648	
OIL	OR-04	FLAME	FR-02
MOTION	FL-02	MECH.	MP-02

Construction

Conductors: finely stranded bare copper

Insulation: specially formulated PVC

Jacket: PVC; black

Application advantage

- International approvals: UL, CSA, <HAR> & CE
- One cable does the job of four, reducing inventory
- One specification for easy and safe installation
- Oil-resistant PVC jacket meets UL Oil Res I/II
- UV-resistant jacket

Complete the installation



SKINTOP® strain relief
page 492



EPIC® pin & sleeve
page 465

Technical data

Minimum bend radius: 4 x cable diameter

Temperature range:
 - UL/CSA SJTO: -25°C to +90°C
 - <HAR> H05VV-F: -30°C to +70°C

Nominal voltage:
 - UL/CSA SJTO: 300V
 - <HAR> H05VV-F: 500V

Test voltage: 2000V

Conductor stranding: Class 5 fine wire

Color code: VDE 0293-308: chart 6, page 681

Approvals:
 UL: SJTO per UL 62
 AWM 21098
 Attributes: UL Oil Res I/II
 sunlight resistant
 -25°C cold bend
 Canada: cUL SJTO
 cRU AWM I/II A/B FT1
 Additional: <HAR> H05VV-F
 CE & RoHS

Part number	Number of conductors incl. ground*	Nominal outer diameter in mm		Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® SL PG thread
18 AWG (17 AWG/1.00 mm²)**						
311802	2	0.265	6.7	13	44	S2109
311803	3	0.283	7.2	19	53	S2111
311804	4	0.304	7.7	25	66	S2111
311805	5	0.348	8.8	32	93	S2111
16 AWG (15 AWG/1.50 mm²)**						
311602	2	0.305	7.7	19	62	S2111
311603	3	0.332	8.4	28	73	S2111
311604	4	0.364	9.2	37	84	S2111
311605	5	0.405	10.3	46	99	S2113

* 2c cable does not include ground

** AWG in parentheses will be written on cable legend per the latest UL 62 requirements

Part number	Number of conductors incl. ground*	Nominal outer diameter in mm		Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® SL PG thread
14 AWG (13 AWG/2.50 mm²)**						
311403	3	0.407	10.3	45	101	S2113
311404	4	0.447	11.4	60	130	S2113
311405	5	0.496	12.6	75	150	S2116

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section.
 If not otherwise specified, all values relating to the product are nominal values.
 Photographs are not to scale and are not true representations of the products in question.

for current information see: www.lappusa.com • www.lappcanada.com