CONSOLIDATED CORDAGE CORPORATION

YOUR #1 SOURCE FOR: 1/64" - 4-1/2" DIAMETER BRAIDED CORD, BUNGEE, NARROW FABRICS, SLINGS, SAFETY NETS, TWINE, TWISTED ROPE, AND RELATED ASSEMBLIES.

CONFIDENTIAL DATA SHEET FOR #18DZ-A

This Data Sheet establishes the requirements for Part number 18DZ-A

Product and Description

Part Number:	18DZ-A
Description:	Flat braided tape manufactured from 100% high tenacity
•	continuous filament polyester yarn. This tape is
	impregnated with a specially formulated self-
	extinguishing synthetic elastomer finish to improve knot
	holding and tying characteristics.

Attributes

Width	0.077" – 0.094"	
Thickness	0.011" – 0.017"	
Minimum Tensile Strength	50 LBS	
Maximum Elongation	40%	
Finish Content	7% – 17%	
Finish	Self-extinguishing synthetic elastomer	
Standard Package	500 YDS	
Military Specification	MIL-T-43435B TYPE-II SIZE-3 FINISH-C	
	OR A-A-52081-C-3	
Other Specifications	BMS13-54 GRADE-B TYPE-1 CLASS-1	
•	FINISH-C	
Standard Colors	Natural or Black	
Other Colors	Available Upon Request	

This Data Sheet meets the requirements for # 18DZ-A.

This Confidential Data Sheet is the sole property of Consolidated Cordage Corporation.

This Data Sheet and the contents of this Data are not to be distributed without written consent of Consolidated Cordage Corporation.

SBA CERTIFIED SDB AND WBE

E-MAIL: SALES@CONSOLIDATEDCORDAGE.COM

1707 AVENIDA DEL SOL

PHONE (561) 347-7247

ISO9001 AND AS9120 CERTIFIED

• WEB: WWW.CONSOLIDATEDCORDAGE.COM

• BOCA RATON, FLORIDA 33432-1742

FAX (561) 394-0380

