

#### **Coast™ Custom Cable**

(310) 639-9473 Phone (310) 763-2225 Fax

Customer Name: IEWC End Use Customer: Sandia National Labs Revision: None

#71 Red/White/Brown

#72 Red/White/Orange

#73 Red/White/Yellow

#74 Red/White/Green

#75 Red/White/Blue

#76 Red/White/Violet

#77 Red/White/Slate

#78 Green/Black

#79 Green/Brown

#81 Green/Orange

#82 Green/Yellow

#83 Green/Blue

#84 Green/Violet

#85 Green/Slate

#86 Green/White

#87 Green/White/Black

#88 Green/White/Brown

#80 Green/Red

Customer P/N: N/A

Customer Revision: N/A

Part Number: 16-1186RA BK199

## **Cable Specification**

# 106/C 24 AWG Unshielded Cable

CONDUCTORS

Wire Size & Type: 24 AWG (19/36) Bare Copper

om. Wire Diameter: 0.025 Insulation Type: Silicone Nom. Ins Thickness: 0.008 Conductor Diameter: 0.041 Tolerance (+/-): 0.002

Note: Printed Stripes Do Not Permanently Adhere To Silicone, Will Rub Off

Colors: #1 Black #36 Black/Slate #2 Brown #37 Black/White #3 Red #38 Black/White/Brown #4 Orange #39 Black/White/Red #40 Black/White/Orange #5 Yellow #41 Black/White/Yellow #6 Green #7 Blue #42 Black/White/Green #43 Black/White/Blue #8 Violet #9 Slate #44 Black/White/Violet #10 White #45 Black/White/Slate #11 Pink #46 Brown/Black #12 White/Black #47 Brown/Red #13 White/Brown #48 Brown/Orange #14 White/Red #49 Brown/Yellow #15 White/Orange #50 Brown/Green #16 White/Yellow #51 Brown/Blue #17 White/Green #52 Brown/Violet #18 White/Blue #53 Brown/Slate #19 White/Violet #54 Brown/White/Black #20 White/Slate #55 Brown/White/Red #21 White/Black/Brown #56 Brown/White/Orange #22 White/Black/Red #57 Brown/White/Yellow #23 White/Black/Orange #58 Brown/White/Green #24 White/Black/Yellow #59 Brown/White/Blue #25 White/Black/Green #60 Brown/White/Violet #26 White/Black/Blue #61 Brown/White/Slate #27 White/Black/Violet #62 Red/Black #28 White/Black/Slate #63 Red/Brown #29 Black/Brown #64 Red/Orange #30 Black/Red #65 Red/Yellow #31 Black/Orange #66 Red/Green #32 Black/Yellow #67 Red/Blue #33 Black/Green #68 Red/Violet #34 Black/Blue #69 Red/Slate #70 Red/White/Black #35 Black/Violet

#89 Green/White/Red #90 Green/White/Orange #91 Green/White/Yellow #92 Green/White/Blue #93 Green/White/Violet #94 Green/White/Slate #95 Blue/Black #96 Blue/Brown #97 Blue/Red #98 Blue/Orange #99 Blue/Yellow #100 Blue/Green #101 Blue/Slate #102 Blue/White #103 Blue/White/Black #104 Blue/White/Brown #105 Blue/White/Red #106 Blue/White/Orange

### ASSEMBLY

Core Cabling: 106/C Cabled (Bunch)

Filler: Fiberglass as required for uniform round construction. Binder: Regular PTFE Tape (100% Coverage, 25% Min. Overlap)

#### **JACKET**

Material Type: Black Silicone Separator: None Nom. Jkt Thickness: 0.056 Cable Diameter: 0.615 Tolerance (+/-): 0.024

## **TESTS**


Test 1: Continuity Test 2: Shorts

Test 3: Physical/Dimensional

# MISCELLANEOUS

Voltage: 30VRMS Temperature: -60°C to 150°C Put Ups: Bulk Reel: Wood or Plastic Weight: TBD

<u>APPROVALS</u> UL/CSA: None





Rev A	Was 106/C 26 AWG, Now 106/C 24 AWG; OD Was 0.555, Now 0.615	MC 2/12/16
UNCONTROLLED	Dimensions in inches unless otherwise specified	UNCONTROLLED COPY
COPY	.XXX = +/005	ONCONTROLLED COFT

Prepared By: Mike Cother

**Customer Approval:** 

Date: 2/5/2016 Configuration Code: 1011222

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the writte consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific encuse application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.