

SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

15-Aug-2016

Product Number: C208C-161C-TFT4

RoHS

Composite Cable - 300V 105°C CSA CMG

O/A Sh 8/C 20/7 STC SR-PVC INS.; Unsh. 1/C 16/26 STC SR-PVC INS.;

Both Cables pulled in & Cabled in One Operation

with Overall PVC Black Jacket

Operating Temperature: -20 to 105°C

Final Diameter :	0.315	inches	8.001	mm
Total Cable Weight:	95	kg/km	64	lbs/1000 ft
Conductor:	8/c 20/7 STC, 1/C 16/26 STC			
Insulation :	SR-PVC FT4			
Shield :	Overall Foil Shield			
Drain \ Ground :	24 AWG 7 Stranded Tinned Copper			
Outer Jacket :	PVC FT4			

Print Notes:

Standard Print: ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C

300V FT4 RU AWM E107863 STYLE 2464 SH 8/C 20 AWG UNSH 1/C 16 AWG

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within

+/- 10%

C208C-161C-TFT4

UNCONTROLLED COPY SpecSheets.rpt Part Spec Rev: 1 08/14/16



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

15-Aug-2016

Additional Information:

Shielded 8/C 20/7 STC DC Resistance: 10.4 Ohms Mutual Capacitance: 30.3 pF/ft Sh. Capacitance: 55.6 pF/ft

Impedance: 70 Ohms Velocity of Prop: 63% Inductance: 1.4 (mH/km)

Conductor Colours 8/c 20 AWG - Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray

Unshielded 1/C 16/26 STC DC Resistance: 4.3 Ohms Mutual Capacitance: 19.2 pF/ft

Impedance: 85 Ohms Velocity of Prop: 65% Inductance (mH/km): 1.3

Conductor Colour 1/C 16 AWG - Red -Located in Center of 20 AWG conductors.

Please contact sales regarding Finished Lengths

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within

+/- 10%

C208C-161C-TFT4

UNCONTROLLED COPY SpecSheets.rpt Part Spec Rev: 1 08/14/16