PRODUCT SPECIFICATION

DESCRIPTION DATE REV **ECN** 2/20/2018 С 17555 ADDED TO PRINT LEGEND.

Parent Number: F14453-


Description: 14 41/30 TC XHHW-2 or SIS VW-1 CSA SIS

Style: UL: XHHW-2 or SIS VW-1 CSA: SIS

Solid Color

DIAMETER: 0.127

 $TOLERANCE \pm : 0.003$



MIN AVG WALL: 0.030

MINIMUM WALL: 0.027

Insulation: XLPE

<u>Print Legend:</u> 14 AWG (2.08mm2) E30117 (PLANT ID CODE) (UL) XHHW-2 SR PRII GRII OR SIS 90C 600V VW-1 -- 156205 CSA SIS 90C 600V -40C FT1 FT2 VW-1

Stranding: 41/30 TC LHL

Voltage: 600V

Temperature: 90C

Notes: 1. Sunlight Resistant per UL 44.

2. Gasoline and Oil Resistant II per UL 44.

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

(<u>Customer</u>	A	DI.	or	01	al	<u>:</u>
Ī							_

Customer Part Nbr(s):

Approved By:

Date: Company Name: Title:



1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115