0.385 ± 0.01 Approved By: Robert Marti

18/11c 16/30 BC TXL Trailer Cable

EA# 11C18BLK 6/19/2017

- .. Inners: $18\ 16/30\ BC\ TXL\ per\ SAE\ J1128,\ \emptyset = 0.078\pm0.003$ "
- around SAE Red & SAE Red/SAE White in Center SAE Purple, SAE Dk Blue, SAE Orange, SAE Yellow, SAE White, 2. Color Pattern: SAE Brown, SAE Gray, SAE Tan, SAE Dk Green,
- 3. Filler: N/A
- 4. Separator: Talc
- 6. Print: INNER CONDUCTORS ARE 125C XLPE AND OUTER JACKET IS UV RESISTANT 105C PVC EA# 11011 (REV#1) MADE Southwire's and does not represent UL's opinion or imply approval. Jacket meets UL 720 hour Sunlight Resistance test. This claim is 0.030", Min Wall Thickness = 0.024", Tube Extruded, UV Resistant 5. Jacket: Black PVC, 105°C, Hardness 85-A, Nom. Wall Thickness =

Revisions:

6/19/2017 DATE

E38022 ECN

DRAWING CREATED

REV

CHANGE

Southwire

Date: 6/20/17

Copperfield

1115 W. Plymouth Street Bremen, IN 46506 By: Rich Tremblay

7. Note: Product will be convoluted