

181-32004



Article Number: 181-32004

Description: Slotted-Wall Wiring Duct, 3" x 2", Non-Adhesive, PVC, Black, 120 ft/carton

Base Data	Local Order Number	181-32004
	Type	SL3X2
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Strong fingers prevent unwanted breaking. • Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. • Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Global Part Name	SL3X2-PVC-BK
	Technical Description	Non-Adhesive
	Short Description	Slotted-Wall Wiring Duct, 3" x 2", Non-Adhesive, PVC, Black, 120 ft/carton
	Product Dimensions	Length L (Imperial)
Length L (Metric)		1.83m
Width W (Imperial)		3.0"
Width W (Metric)		76.2mm
Width W2 (Imperial)		3.0"
Width W2 (Metric)		76.2mm
Width W3 (Imperial)		0.4"
Width W3 (Metric)		10.2mm
Width W4 (imperial)		1.0"
Width W4 (metric)		25.4mm
Width W5 (imperial)		1.62"

181-32004



Product Dimensions	Width W5 (metric)	41.1mm
	Width W6 (imperial)	1.0"
	Width W6 (metric)	25.4mm
	Height H (Imperial)	2.07"
	Height H (Metric)	52.60mm
	Mounting Hole Centers (Imperial)	4.0"
Material and Specifications		
	Material	Polyvinylchloride (PVC)
	Material Shortcut	PVC
	Flammability	Self-Extinguishing
	Operating Temperature	+122°F (+50°C)
	ROHS Compliant	Yes
	Certification/Specification WEB	CSA, UL
UL Recognized (US)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	120ft
	Package Quantity (Metric)	36.6m
	Customs Number(Schedule B)	3925900000