Description: Six 20 AWG Conductors Overall Fleece and PU Jacket

Date: 10/16/17

JM Part Number: TBD Reference: TBD

Cable Assembly Tail I 5 1/4"-31 1/2" -All Dimensions Are Nominal 27 1/2" Tail 2

Components Three 20 AWG Twisted Pairs

Conductor: 20 AWG, 26/34 bare copper Insulation: .011" nominal wall of Hytrel (see color code)

.060"

Pair: Two Conductors twisted together

Overall Cable

Cabling: Three Twisted Pairs cabled together, No Fillers Separator: Fleece tape Jacket: .045" nominal wall of Black Pressured Polyurethane

<u>3</u>

Print

NONE

Color Code

Pair 1: White and Brown Pair 2: Green and Yellow Pair 3: Grey and Pink

Coll Regulrements

Retracted Coil Length: 31 1/2 inches Extended Coil Length: 126 inches Nominal Coil Diameter: 1.098 inches

Tail 1 Length: 5 1/4 inches (Blunt Cut)
Tail 2 Length: 27 1/2 inches (Blunt Cut)

Temperature: -25°C to 80°C Voltage: 300V

Requirements

Approvals: NONE

HPPROVED Bom's. Mare Murrou 10-26-17

Rev.0 Initial Issue

Fig. V3PR26-26stp-HYT-PU-Cal/Cord