	÷
-	1
120	
12-1	
L	
	Ī

DATE APPROVAL

REVISIONS

DEBCKWYTON

"Their a preprietary design or drawing of Knotoo Elec- tronics, Inc., delivered solely for fransecting business." In the control of the contr	
Enc., and malpiant malpiant may not copy, reproducts.	ı
transmit or discions it or any information hereon to others	ı
without angular comparison of Mantley Charlesons in the "	

· · · · · · · · · · · · · · · · · · ·					
WIRE SIZE AWG 22 STRANDS 19/34 PLATED SILVER					
NUMBER OF CONDUCTORS 2					
INSULATION MATERIAL TEE (TEFLON)					
COLORS YELLOW (4) BLUE (6)					
SHIELDED YES X NO .					
SHIELD TYPE BRAIDED X FOIL MATERIAL COPPER PLATED SILVER					
JACKET MATERIAL TEFLON COLOR WHITE					
JACKET TYPE WRAPPED X EXTRUDED					
OVER ALL DIAMETER -145					
OPERATING TEMP RANGE -85°F TO +392°F (-65° C to + 200°C)					
IN ACCORDANCE WITH MIL-SEC MIL-W- 16878 TYPE E					
SPECIAL REQUIREMENTS JACKET TO BE WOUND LOOSE ENOUGH TO BE STRIPABLE WITH A MINIMUM DEGREE OF DIFFICULTY. THE FUSING OPERATION MUST NOT BOND JACKET TO SHIELD OR CONDUCTOR TO CONDUCTOR.					

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE IF EXPORTED FROM THE UNITED STATES MUST BE IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW IS PROHIBITED.

MATERIAL				
HEAT TREAT	FRACT ± 1/32 ANG ± 1/2"	DRAWN M.T. 11-76	KAVLICO ELECTRONICS, INC.	
FINISH	✓ FIN'SH PER MIL-STD-10 ON ALL /AACHINED SURFACES	STRESS CHECK		
PART TO BE CLEAN AND OIL FREE . REMOVE BURRS & BREAK SHARP EDGES FILIET RADII TO BE	DIMENS ONING & TOLERANCING SY 4BOLS PER MIL-STD-8 FLAT 1655 & STRAIGHTNESS	APPD Thelen 11/76	CABLE	
PERPENDICULAR SURFACES TO BE WITHIN .005 DIAMETERS ON COMMON & TO BE @ WITHIN THE TO BE IN ACCORDANCE WITH MIL-S-7742	ANGULAR 1 PERPENDICULAR	APPROVAL	SIZE CODE IDENT NO. 12-120	
DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIF	POSITION P RUNOUT APP	APPROVAL	SCALE WEIGHT SHEET OF	