

Coast™ Custom Cable

Tel: (908) 925-8000 E-mail: coast@alphawire.com
Distributor: IEWC

IP Owner: COBO Int.

Part Number: 18-2229 BK199

Revision: None

Customer P/N: **N/A**Customer Revision: **N/A**

Cable Specification

2/C 18 AWG Unshielded Cable

CONDUCTORS

Wire Size & Type: 18 AWG (19/30) Tinned Copper

Nom. Wire Diameter: 0.046

Insulation Type: XL Polyethylene (Moisture Cured), Designed to meet SAE J1128 Standards for GXL Type, 125°C Dry

Nom. Ins Thickness: 0.021

Conductor Diameter: 0.088 0.098 Max.

Colors: Yellow and Green

ASSEMBLY

Core Cabling: 2/C 18 AWG Twisted
Nom. Lay Length: 0.88 +/- 0.118
Lay Direction: Left (Clockwise)

Filler: None Binder: None

JACKET Will Show Convolutions (As Sample)

Material Type: Black PVC
Separator: None
Nom. Jkt Thickness: 0.040
Nominal Diameter: 0.255

Tolerance (+/-): 0.010

TESTS

Test 1: Continuity
Test 2: Shorts

Test 3: Physical/Dimensional

MISCELLANEOUS

Put Ups: Bulk, May Contain Multiple Lengths Per Reel

Reel: Wood or Plastic

Colors: Munsell® Wire & Cable Limits of Deviation

ENVIRONMENTAL COMPLIANCE

RoHS: European Directive 2011/65/EU(ROHS2) and amending Directive 2015/863/EU

APPROVALS Final Product: None

Note: Cable drawing is representative only and may not match the specific configuration of the final product.

Dimensions in inches unless otherwise specified

Prepared By: Mike Cother

Date: 9/12/2018

Customer Approval:

Title:

n Engineer

Date:

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.