DATEREVECNDESCRIPTION9/19/2018CE40991Updated the style section.

PRODUCT SPECIFICATION


Parent Number: FMC021-

Description: 0.35mm2 7/.25mm TC Thin Wall 3TAE ES-

AU5T-1A348-AA Ford Global Spec FLRYW-A

DIAMETER: 0.051

 $TOLERANCE \pm : 0.004$



NOM WALL: 0.010

MINIMUM WALL: 0.008

Stranding: 7/.25mm TC LHL

Style: Ford: ES-AU5T-1A348-AA 3TAE; ISO 6722-1; DIN 76722 FLRY

0.5-A T125

Insulation: 125C PVC

Print Legend: NO PRINT

Voltage: Nominal system voltage of 60 V rms or less in automotive electrical harnesses.

Temperature: -40C to +125C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

<u>Customer</u>	Approval	:

 Southwire

Copperfield®

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115