C0602A DIFF CC

CONDI	JCTORS:	

#24 7/32 TINNED COPPER INSULATED WITH .010" SR PVC

PAIRS:

TWIST TWO (2) CONDUCTORS TOGETHER

CABLING:

CABLE THREE (3) PAIRS TOGETHER

TAPE SHIELD:

ALUMINUM/POLYESTER TAPE SHIELD

FOIL FACING OUT, 25% OVERLAP, 100% COVERAGE

DRAIN:

#24 7/32 TINNED COPPER DRAIN WIRE

JACKET:

.035" CHROME PVC

NOM OD:

.233"

PRINT IN WHITE:

E151405 24 AWG TYPE CM 105°C (UL)...AWM 2464...C(UL) TYPE CMG

(1331)

FT-4...105°C 300V...CE...ROHS

COLOR CODE PAIRS:

1) BLACK-RED PAIRED WITH RED

2) BLACK-WHITE PAIRED WITH WHITE

3) BLACK-GREEN PAIRED WITH GREEN



ROHS COMPLIANT

YES

I HAVE REVIEWED ABOVE SPECIFICATION AND IT CONFORMS TO ITEM ORDERED UNDER PO#

NOTE AND EXCEPTIONS HERE >

SIGNED: CTE626A-EX

DATED: 3-14-19

10/24/2018 PAGE: 1 OF 1