18/3 Type SVT



PRODUCT DATA SHEET

SVT is a light-duty service cord, rated at 300 volts with a temperature range up to 105°C. With extra-flexible stranding, PVC primary insulation, and PVC jacket, this cable is designed for indoor use where reduced cable outer diameter is preferred.

Design Number10136Part Number32113355Customer NumberN/A

CONSTRUCTION

Conductor: Stranded bare copper Conductor Size: 18AWG(41/34) Insulation: Polyvinyl chloride (PVC) Insulation Avg. Thickness: 0.015"(Nom.) Insulation Diameter: 0.087"(Nom.)


Filler: PP Yarn
Separator: Paper

Jacket Material: Polyvinyl chloride (PVC)
Jacket Avg. Thickness: 0.030"(Nom.)
Overall Diameter: 0.256"(Nom.)

Jacket Color: Grey

Print Legend:

E486041 IH (UL) SVT VW-1 105°C 300V 3/C 0.823 mm² (AWG 18) c(UL) SVT FT2 105°C 300V 3/C 18 AWG (0.823 mm²)



Color Code: 1. Black 2. White 3. Green/Yellow

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 105° C

Operating Voltage: 300V

Conductor Resistance @ 25°C: 22.8 Ω/km Max

Flame Test: UL VW-1 and CSA FT2

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU **Approvals:** UL, the basic standard is UL 62 "Flexible Cords and Cables" c(UL) approved to meet CSA standard C22.2, flexible cords

Application: In accordance with Article 400 of the NEC, applications include vacuum cleaners, household food appliances, home entertainment appliances, and power cords for light-duty equipment

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2022/10/19	Initial release
Cunn	And I linu	Annual A Hillians
Created L. Jian		Approved A. Huang

