

1. CONDUCTOR:

- 1.1 Size and Material: 10 105/30 AWG tin-plated copper wire.
- 1.2 O.D.: .115" nom.

2. INSULATION:

- 2.1 Extruded flame retardant silicone rubber.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .205" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:


- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C

4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 3212.
- 4.2 CSA standard C22.2 No.210.2-M90 (AWM), Class I Group A.

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.								 This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: 		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourintl.com				
810									Date: October 18, 2002						
									Verified: 		Description: XSF45Z10105/30-X				
									Date: October 18, 2002						
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									 A member of The Marmon Group of companies		Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F00101-X