



Specification Sheet

Lake Cable Part #: C244CT-ASC

DEWC# 63644 32130944

Description:

24 AWG 4 conductor 7 strand tinned copper wire, PVC insulation, unshielded, and an overall

PVC jacket.

1. Conductor

1.1. AWG Size & Stranding: 24 AWG 7 Strand Class B 1.2. Material: Annealed Tinned Copper

1.3. Conductor Count: 4 Conductors

2. Insulation

2.1. Material: Polyvinylchloride

2.2. Wall Thickness: 0.010"

2.3. Diameter: $0.043" \pm 0.002"$

2.4. Color Code: Black, White, Red, Green

3. Assembly

3.1. Nominal Lay Length: 2.00" LHL (6.00 Tw/Ft)

3.2. Shield: N/A 3.3. Drain Wire: N/A

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall thickness: 0.032"

4.3. Diameter: 0.168" ± 0.015"

4.4. Color: Gray 4.5. Ripcord: N/A

4.6. Weight: 16 Lbs/Mft

5. Markings*

5.1. Type: Cable permanently identified via surface inkjet print

5.2. Legend: ASCENT E478021 24AWG 4C 75C C(UL)US TYPE CMR SUN RES FT4 OR AWM

2464 300V 80C OR AWM 2576 150V 80C "ROHS COMPLIANT" MADE IN USA

5.3. Footage Markers: Yes

6. Standards

6.1. Cable suitable for installation under NEC (NFPA 70) articles 800 guidelines

- 6.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 6.3. C(UL)US listed as CMR per UL standard 444 and per CSA C22.2 No. 214-17
- 6.4. UL recognized component as AWM 2464 & 2576, per UL standard 758

6.5. Cable meets UL 1685 (Vertical) flame test

- 6.6. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
- 6.7. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated January 15, 2019
- 6.8. Operating Voltage: 300V RMS
- 6.9. Made in the USA
- 6.10. WARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION
*Client expressly indemnifies Lake Cable, LLC for any liabilities relating in any way to Lake Cable's placement
of markings on the product, when such markings are specified for such placement by the client