UL CMR/2464 24AWG/10C, Foil Shielded Cable ASCENT



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 800 guidelines. Cable is suitable for installation in Canada under Section 60 of CEC, Part I. Internal wiring or external interconnection of electronic equipment.

Design Number 10375 **Part Number** 32130957 **Customer Number** N/A

CONSTRUCTION

Conductor: Stranded tinned copper Conductor Size: 24AWG(7/32) **Insulation:** Polyvinyl Chloride Insulation Thickness: 0.010"(Nom.) **Insulation Diameter:** 0.043"(Nom.) Cable Lay Length: 2.50"(Nom.)


Tape: Al-mylar (Aluminum side facing out), 100% coverage Drain Wire: Stranded tinned copper, 24AWG 7 Strands

Jacket Material: Polyvinyl Chloride Jacket Thickness: 0.032"(Nom.) Overall Diameter: 0.238"(Nom.)

Jacket Color: Gray

Print Legend (Footage Markers):

ASCENT E478021 24AWG 10C SHIELDED 75C C(UL)US TYPE CMR SUN RES FT4 OR AWM 2464 300V 80C "ROHS COMPLIANT" MADE IN USA



Color Code: Blue, White, Black, Yellow, Purple, Gray, Red, Green Brown, Orange

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 80°C

Operating Voltage: 300V Weight: 34 Lbs/Mft

Flame Test: Cable meets (UL) 1685 (Vertical)

SAFETY CHARACTERISTICS

Approvals: UL AWM Style 2464 per UL standard 758 C(UL)US listed as CMR per UL standard 444 and per CSA C22.2 No. 214-17

RoHS Compliant: European Directive 2015/863/EU

REACH Compliant: Regulation (EC) No 1907/2006 Updated Jan.15, 2019

Application: Internal wiring or external interconnection of electronic equipment

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History			
00	2020/09/08	Initial Release	
Created L. Jian		Approved A. Huang	



