UL CMR/2464 18AWG/25C, Gray



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 800 guidelines. Cable is suitable for installation in Canada under Section 60 of CEC, Part I. Internal wiring or external interconnection of electronic equipment.

Design Number10425Part Number32131017Customer NumberN/A


CONSTRUCTION

Conductor:Stranded tinned copper Conductor Size: 18AWG(16/30) Insulation: Polyvinyl Chloride Insulation Thickness: 0.016"(Nom.) Insulation Diameter: 0.078"(Nom.) Cable Lay Length: 7.00"(Nom.) Jacket Material: Polyvinyl Chloride Jacket Thickness: 0.032"(Nom.) Overall Diameter: 0.535"(Nom.)

Print Legend (Footage Markers):

Jacket Color: Gray

ASCENT E478021 18AWG 25C 75C C(UL)US TYPE CMR SUN RES FT4
OR AWM 2464 300V 80C OR AWM 2576 150V 80C "ROHS COMPLIANT"
MADE IN USA



Color Code:

Black, Red, White, Green, Orange, Blue, Red/Black, Orange/Black, Green/Black
Blue/Black, Black/White, Green/White, White/Black, Black/Red, Blue/White,
White/Red, Orange/Red, Blue/Red, Red/Green, Orange/Green, Black/Red/White,
Red/White, White/Black/Red, Red/Black/White, Green/Black/White

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 80°C Operating Voltage: 300V Weight: 207 Lbs/Mft

Flame Test: Cable meets (UL) 1685 (Vertical)

SAFETY CHARACTERISTICS

Approvals: UL AWM Style 2464, 2576 per UL standard 758 C(UL)US listed as CMR per UL standard 444 and per CSA C22.2 No. 214-17

RoHS Compliant: European Directive 2015/863/EU

REACH Compliant: Regulation (EC) No 1907/2006 Updated Jan.15,2019

Application: Internal wiring or external interconnection of electronic equipment

All trademarks are property of their respective owners. All specifications are subject to change.

| Revision History | | |
|------------------|------------|-------------------|
| 00 | 2020/10/19 | Initial Release |
| | | |
| | | |
| Created L. Jian | | Approved A. Huang |

