



PRODUCT INFORMATION SHEET

DELPHI M3382

150°C - Cable Expanded Duty Fusible Link

Features

Copper Conductors per ASTM B3
Insulation Material: 150°C XLPE
RoHS Compliant

Applications

Road Vehicle Applications where nominal system voltage is 50 volts or less
Temperature -40°C to 150°C

Compliance

Delphi M3382 Except Color
SAE: J1128 HTS
SAE: J 156

Product Options

Colors Black, Blue, Gray, Orange(Rust), and Red
Packaging Options: Drums or reels, various sizes and disposal or recyclable

Conductor Size	Number of Strands	Minimum Average Strand Diameter	Strip Force, Minimum	Insulation Thickness, Minimum	Cable OD, Minimum	Cable OD, Maximum
mm ²		mm	N	mm	mm	mm
0.35	7	0.25	10	0.64	2.44	2.70
0.5	19	0.19	10	0.63	2.64	2.90
0.8	16	0.25	20	0.66	2.93	3.19
1	19	0.28	20	0.72	3.31	3.57
2	19	0.35	20	0.74	3.76	4.02
3	19	0.44	20	0.83	4.48	4.74
5	19	0.56	20	0.86	5.13	0.39
8	37	0.50	20	0.91	5.73	6.13