Plugs & connectors




Heavy duty grade vinyl plugs & connectors

Product description

2-pole, 3-wire grounding 15A & 20A, 125V/AC 15A & 20A, 250V/AC

Design features

- · Solid brass plug blades are firmly embedded
- Vinyl plugs and connectors resist chemical attack and are less brittle in extremely low temperatures
- · Vinyl angle plugs have eight possible positions for maximum convenience
- · Terminal screws backed out and ready for wiring



- Terminals in individual chambers to positively insulate conductors
- Terminal screw clamps are designed to contain wire and prevent binding
- · Combination Slot/Phillips head mounting and terminal screws for installation flexibility (Slot/ Robertson screws in Canada where available)



4867ANW



4229

Vinyl plugs & connectors





Rating					Plug	Connector	_	
Α	V/AC	Description	Cord diameter	Color	catalog no.	catalog no.		
15	125	NEMA 5-15, straight body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4867	□ 4887	•	
15	125	NEMA 5-15, angled body	0.25-0.66" (6.4-16.6mm)	Υ	☐ 4867AN		•	
15	125	NEMA 5-15, angled body	0.25-0.66" (6.4-16.6mm)	W	☐ 4867ANW		•	
20	125	NEMA 5-20, straight body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4409	□ 4228	•	
Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 4228								

Vinyl plugs & connectors





R	ating				Plug	Connector	<i>□</i> =
Α	V/AC	Description	Cord diameter	Color	catalog no.	catalog no.	
		NEMA 5-20, angled body	0.25-0.66" (6.4-16.6mm)	Y	□ 4409AN	'	•

Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 4227 & 4229

Vinyl plugs & connectors





				Plug	Connector	<i>a</i> =
//AC	Description	Cord diameter	Color	catalog no.	catalog no.	_
250	NEMA 6-15, straight body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4866	□ 4227	•
250	NEMA 6-15, angled body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4866AN		•
250	NEMA 6-20, straight body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4509	□ 4229	•
250	NEMA 6-20, angled body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4509AN		•
2	50 50 50	NEMA 6-15, straight body NEMA 6-15, angled body NEMA 6-20, straight body	50 NEMA 6-15, straight body 0.25-0.66" (6.4-16.6mm) 50 NEMA 6-15, angled body 0.25-0.66" (6.4-16.6mm) 50 NEMA 6-20, straight body 0.25-0.66" (6.4-16.6mm)	50 NEMA 6-15, straight body 0.25-0.66" (6.4-16.6mm) Y 50 NEMA 6-15, angled body 0.25-0.66" (6.4-16.6mm) Y 50 NEMA 6-20, straight body 0.25-0.66" (6.4-16.6mm) Y	50 NEMA 6-15, straight body 0.25-0.66" (6.4-16.6mm) Y □ 4866 50 NEMA 6-15, angled body 0.25-0.66" (6.4-16.6mm) Y □ 4866AN 50 NEMA 6-20, straight body 0.25-0.66" (6.4-16.6mm) Y □ 4509	50 NEMA 6-15, straight body 0.25-0.66" (6.4-16.6mm) Y 4866 4227 50 NEMA 6-15, angled body 0.25-0.66" (6.4-16.6mm) Y 4866AN 50 NEMA 6-20, straight body 0.25-0.66" (6.4-16.6mm) Y 4509 4229

Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 4227 & 4229

Color ordering information:

Y (Yellow), W (White)



Dimensional information: B-70 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page F-21