

Description: Four Conductor 18 AWG,

Overall PVC Jacket

GENERAL PRODUCT SPECIFICATION Phone 800-316-8877 Fax 978-368-1275 www.jamesmonroewire.com


Nom OD

Create Date: 04/09/2025

JM Part No: TBD

Reference:

Cable Diagram



Components Four 18 AWG, PVC Insulated Conductors

Conductor: 18 AWG, 16/30 tinned copper

Insulation: .030" nominal wall of PVC (see color code) .105"

Overall Cable Construction

Cabling: 4 conductors cabled together

Jacket: .035" nominal wall of Black PVC .323"

Print White Inkjet

E231303 4/C 18 AWG 600V (UL) BOAT CABLE BC-5W2 105C DRY 75C WET OIL RES

Color Code Striped conductors

1. Blue/White 2. Red/White 3. Green/Red 4. Green

Requirements

Temperature: 105°C

Voltage: 600V

Cable Weight: 56 lbs/Mft
Copper Weight: 20 lbs/Mft

Approvals:

UL Boat Cable

Materials are RoHS 3 Compliant (2011/65/EU & EU 2015/863)

Written By:	ka/ba	04/09/2025	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				