



Product: <u>5202UE</u> ☑

Security & Sound, #16-4c, BC, CMR

Product Description

Security & Sound Cable, Riser-CMR, 4-16 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Product Overview	
Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls	
Construction Details	
Conductor	
Element No. of Elements Size Stranding Material	
Conductor(s) 4 16 AWG 19x29 BC - Bare Copper	
nsulation	
Element Material Nom. Thickness Nom. Insulation Diameter Color Code	
Conductor(s) PO - Polyolefin 0.008 in (0.20 mm) 0.073 in (1.9 mm) Black, Red, White, Green	
Outer Jacket	
Material Nom. Thickness Nom. Diameter Ripcord	
PVC - Polyvinyl Chloride 0.017 in (0.43 mm) 0.210 in (5.33 mm) Yes	
Overall Cable Diameter (Nominal): 0.210 in (5.33 mm)	
Electrical Characteristics	
Electricals	
Element Nom. Conductor DCR Nom. Capacitance Cond-to-Cond Max. Current	
Conductor(s) 4.2 Ohm/1000ft 23 pF/ft (75 pF/m) 5.0 Amps per conductor @ 25°C	
Voltage	
UL Voltage Rating	
300 V (CMR)	
Mechanical Characteristics	
Temperature	
UL Temperature Operating	
75°C -20°C to +75°C	
Bend Radius	
Stationary Min. Installation Min.	
2.1 in (53 mm) 2.1 in (53 mm)	
Max. Pull Tension: 117 lbs (53.1 kg) Duils Oath Multicht 40 lbs (40000)	
Bulk Cable Weight: 42 lbs/1000ft	

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6202UE

History

Update and Revision:

Revision Number: 0.445 Revision Date: 03-04-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
5202UE 010500	Black			612825157960	С
5202UE 010U1000	Black			612825157953	
5202UE 0081000	Gray			612825157922	С
5202UE 008500	Gray			612825157939	
5202UE 008U1000	Gray			612825336587	
5202UE 008U500	Gray			612825157915	
5202UE.00152	Gray	Reel	152 m	8719605008107	
5202UE.00305	Gray	Reel	305 m	8719605008114	
5202UE.00U305	Gray	Reel	305 m	8719605008121	
5202UE 009U1000	White			612825157946	

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.