

Lamp Cord Type SPT

60°C, 300 Volt, UL/CSA

Product Construction:

Conductor:

- 18 and 16 AWG fully annealed bare or tinned copper

Insulation:

- Premium-grade, color-coded PVC
- Temperature range: -20°C to +60°C
- Color code: See chart below

Jacket Marking:

- E# (UL) (NO. COND) (SIZE) (mm²) SPT-1 (or SPT-2) 60°C FT2 300 VOLT CSA LL69381 RoHS

Applications:

- Small appliances
- Lamps
- Radios
- Jukeboxes

Industry Approvals:

- UL Listed
- CSA Certified
- RoHS Compliant

Packaging:

- 250' (76.2 m) spools
- Other put-ups available on special order

JACKET COLOR CODE CHART

A	Black or White or Brown
B	Clear Silver (tinned copper)
C	Clear Gold
D	Clear



TYPE SPT-1

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOM. INSULATION THICKNESS		NOMINAL O.D.		CURRENT AMPS ⁽¹⁾	APPROX. NET WEIGHT LBS/M ⁽⁵⁾	JACKET COLOR CHART
				INCHES	mm	INCHES	mm			
02301	2	18	41/34	0.030	0.76	0.107	2.72	10	22	A
						X	X			
						0.210	5.330			
02304	2	18	41/34	0.030	0.76	0.107	2.72	10	22	D
						X	X			
						0.210	5.330			
02305	2	18	41/34	0.030	0.76	0.107	2.72	10	22	C
						X	X			
						0.210	5.330			
02306	2	18	41/34	0.030	0.76	0.107	2.72	10	22	B
						X	X			
						0.210	5.330			

TYPE SPT-2

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOM. INSULATION THICKNESS		NOMINAL O.D.		CURRENT AMPS ⁽¹⁾	APPROX. NET WEIGHT LBS/M ⁽⁵⁾	JACKET COLOR CHART
				INCHES	mm	INCHES	mm			
02303	2	16	65/34	0.045	1.14	0.155	3.94	13	37	A
						X	X			
						0.295	7.490			

⁽¹⁾ Ampacities based on NEC Table 400.5(A)(1).

⁽⁵⁾ Actual shipping weight may vary.