

python®

Hinged Plugs and Connectors



When it comes to the demanding nature of today's commercial and industrial electrical environments, ruggedness and ease of installation are the features you look for first in any line of plugs and connectors. Python 15 and 20 Amp straight-blade plugs and connectors have the ability to survive in the toughest conditions and the roughest handling. Python's exceptional design features meet your needs for a quick, cost-effective, easy-to-wire plug and connector system.


Python's high performance plugs and connectors are the ideal choice for hundreds of quick set-up, fast break-down applications across industrial, hospital, healthcare, commercial, OEM, retail, and construction environments.





Specifications

Electrical Specifications						
Temperature Rise	Max 30°C after 250 cycles overload at 200 percent rated current					
<u>'</u>						
Dielectric Voltage	Withstands 2000V per UL498					
Current Interrupting Certified for current interrupting at full rated current						
Environmental Specifications						
Flammability	Rated V-2 per UL94					
Operating Temperature	-40°C (-40°F) to 60°C (140°F)					
Material Specifications						
Housing	Super Tough Nylon					
Terminal Cover	Clear Thermoplastic					
Clamp Insert	Nylon					
Blades/Contacts	Solid Brass					
Terminal Screws	Plated Steel					
Terminal Clamps	Galvanized Steel					
Assembly Screws	Zinc-plated Steel, #6-32					
Mechanical Specifications						
Terminal ID	Brass-Hot, Green-Ground, Silver-Neutral					
Terminal Accom.	18-10 AWG					
Torque Range	12-14 Inch lbs					
Product ID	Ratings and NEMA I.D. permanently marked on device					
Cord Range	.250" to .700"					
Standards and Certifications						
NEMA	WD-6					
ANSI	C-73					
UL	498					
CSA	C22.2 No. 42					
NOM	057					
Warranty						
Product Warranty	Two-year Limited Warranty					

Dimensions







Ordering Information

Amps	Volts	NEMA	Catalog Number	Grade	Device Type	Color
15	125	5-15	5256-VY	Industrial Grade	Plug	Yellow
			5256-VB	Industrial Grade	Plug	Black
			5256-VGY	Industrial Grade	Plug	Gray
			5256-VA	Industrial Grade	Angle Plug	Yellow
			8256-V	Hospital Grade	Plug	White
			5259VY	Industrial Grade	Connector	Yellow
			5259-VB	Industrial Grade	Connector	Black
			5259-VGY	Industrial Grade	Connector	Gray
			8259-V	Hospital Grade	Connector	White
	250	6-15	15656-VY	Industrial Grade	Plug	Yellow
			8656-V	Hospital Grade	Plug	White
			15659-VY	Industrial Grade	Connector	Yellow
			8659-V	Hospital Grade	Connector	White
20	125	5-20	5356-VY	Industrial Grade	Plug	Yellow
			5356-VB	Industrial Grade	Plug	Black
			5356-VA	Industrial Grade	Angle Plug	Yellow
			8356-V	Hospital Grade	Plug	White
			5359-VY	Industrial Grade	Connector	Yellow
			5359-VB	Industrial Grade	Connector	Black
			8359-V	Hospital Grade	Connector	White
	250	6-20	5456-VY	Industrial Grade	Plug	Yellow
			5456-VA	Industrial Grade	Plug Angle	Yellow
			8456-V	Hospital Grade	Plug	White
			5459-VY	Industrial Grade	Connector	Yellow
			8459-V	Hospital Grade	Connector	White

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 • Fax: 1-800-832-9538 • Tech Line (8:30AM-7:00PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Blvd, Pointe-Claire, QC H9R 1E9 Telephone: 1-800-469-7890 • Fax: 1-800-563-1853

Leviton S. de R.L. de C.V.

Lago Tana 43, Col. Huichapan, Miguel Hidalgo, CP 11290 México DF Telephone: (+52) 55-5082-1040 • Fax: (+52) 55-5386-1797 • www.leviton.com.mx

