



| ADVANCED CABLE TIES PART NUMBER | BUNDLE DIAMETER | | A IN (mm) +/- .125 (3.175mm) | B IN (mm) +/- .005 (.127mm) | C IN (mm) +/- .005 (.127mm) | D IN (mm) +/- .020 (.508mm) | E IN (mm) +/- .020 (.508mm) | F IN (mm) +/- .030 (.762mm) | MIN LOOP TENSILE LBS (n) | ANSI/UL 94 MH FLAMABILITY RATING | PLENUM RATING |
|------------------------------------|--------------------|---------------------|---------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------|----------------------------------------|---------------|
| | MIN IN (mm) | MAX IN (mm) | | | | | | | | | |
| AP(R, L)-05-40-9 | .0625 (1.587mm) | 1.437 (36.423mm) | 5.840 (148.336mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-05-40-0 | .0625 (1.587mm) | 1.437 (36.423mm) | 5.840 (148.336mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-08-40-9 | .0625 (1.587mm) | 2.375 (60.325mm) | 8.875 (225.425mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-08-40-0 | .0625 (1.587mm) | 2.375 (60.325mm) | 8.875 (225.425mm) | .049 (1.244mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-11-40-9 | .0625 (1.587mm) | 3.375 (85.725mm) | 10.968 (278.587mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-11-40-0 | .0625 (1.587mm) | 3.375 (85.725mm) | 10.968 (278.587mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-14-40-9 | .0625 (1.587mm) | 4.000 (101.6mm) | 14.250 (361.950mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |
| AP(R, L)-14-40-0 | .0625 (1.587mm) | 4.000 (101.6mm) | 14.250 (361.950mm) | .054 (1.371mm) | .140 (3.556mm) | .240 (6.096mm) | .175 (4.445mm) | .250 (6.350mm) | 40 (178) | V-2 | AH-2 |



ADVANCED CABLE TIES – 40 LB. (178n) INTERMEDIATE SERIES
CABLE TIES

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL

MATERIAL:

NYLON 6/6 POLYAMIDE

SHEET 1 OF 1

REV.: A

DRAWING NO.: 40-A

| | | | | | | | | | |
|-----|---------|----|-----|---------|-----------------|----------|-----------|-------|-------|
| A | 4/15/14 | JA | KT | KT | INITIAL RELEASE | DRAWN BY | DATE | CHECK | SCALE |
| REV | DATE | BY | CHK | APPROVE | DESCRIPTION | JA | 4/15/2014 | KT | NONE |

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.